

Connected to: #00197868 Firmware version: 1.02

Error code: 0x0080

Status Errors Channel Settings Serial Settings Sequence Script

Code Run script on startup Script: 200 of 8192 bytes used Subroutines: 126 of 126 levels used Stack

```

1
2
3
4 ### Sequence subroutines: ###
5
6 # Demo 1
7 sub Demo_1
8   500 5480 6914 5945 5363 5848 7185
9   0 0 0 0 0 0 frame_0..11 # Frame 0
10  500 4452 6080 6488 6294 5596 5228 frame_0..5 # Frame 1
11  500 6701 6798 5324 4704 5014 6701 frame_0..5 # Frame 2
12  500 7069 4433 5092 4549 4898 4879 frame_0..5 # Frame 3
13  500 4297 5751 6681 frame_1..2..5 # Frame 4
14  500 5111 7030 6429 4859 5538 6000 frame_0..5 # Frame 5
15  500 6895 6255 4588 frame_1..3 # Frame 6
16  return
17
18 sub frame_0..11
19   11 servo
20   10 servo
21   9 servo
22   8 servo

```

#	Value
21	
20	
19	
18	
17	
16	
15	
14	
13	
12	
11	
10	
9	
8	
7	
6	
5	
4	
3	
2	
1	
0	

Fig.7

Stop Script Run Script Step Script Restart Script Scroll to follow script View Compiled Code...

Save Frame 7

Apply Settings

Windows taskbar showing 'Inicio' button, a row of application icons (including Internet Explorer, Word, PowerPoint, etc.), and a system tray with the time '03:35 p.m.', date 'Viernes 02/06/2023', and system icons.